Da	ate	e:.	 	 							 						
		•••	 	 ٠.	••		٠.	٠.	•••		 • •	• • •	 ٠.	٠.			
••••		•••	 	 	• •	• • •	٠.	• •	• •	• • •	 • •	• • •	 ٠.	• •	• •	• •	

Dear Sir,

Sealed Tenders are hereby invited from Manufacturers, Representatives or their Accredited Agents for the supply of 5000 M/T Web Offset Newsprint Paper in Reels to be delivered from November 2004 onwards conforming to the undermentioned basic specifications.

1. Reel Width - 711 mm

2. Substance - 48.8 GSM & 45 GSM

3. Tear Strength - M/D - Not less than 300 mN

C/D - Not less than 325 mN

4. Opacity - Not less than 93%
5. Brightness - Not less than 60%
6. Reel Diameter - 914 - 1016 mm

7. Core Diameter - 76 mm8. Moisture Contents - 7% - 8%

- Tenders should be submitted only on Tender Documents available at Imports Dept. of The Associated Newspapers of Ceylon Ltd. on payment of a non-refundable fee of Rs. 1000/= in Cash. Documents will be issued during Office hours until 3.00 p.m. on 08th November 2004.
- 2. Breakdown of the C.I.F. Price Per MT should be indicated as Cost, Insurance and Freight Charges.
- 3. Tender will be closed at 2.30 p.m. on 10th November, 2004 and will be opened in the presence of Tenderers at 3.00 p.m. on the same day.
- **4.** A Bid Bond of Rs. 100,000/= valid for 2 months in the form of a Bank Guarantee issued by a reputed Bank in Sri Lanka should be submitted along with the Tender.
- The successful Tenderers will be required to forward a Performance Bond equivalent to 2% of the total value of the order.
- 6. Sealed Tenders along with the Bid Bond should be sent under Registered Cover addressed to The Manager Imports, The Associated Newspapers of Ceylon Ltd., Lake House, 35, D.R. Wijewardene Mawatha, Colombo 10, to reach before the closing time, marked "TENDER FOR THE SUPPLY OF WEB OFFSET NEWSPRINT PAPER" on the top left corner of the envelope.
- 7. Separate documents should be used for each offer.
- 8. Offfers from new sources will be considered only after testing the quality of their samples.
- **9.** Offers not in conformity with our requirements will be rejected.
- **10.** The Associated Newspapers of Ceylon Ltd., reserves the right to reject any or all offers without assigning any reasons what-so-ever.
- **11.** Charges of Rs. 1000/= or equivalent amount by Cheque to be forwarded along with the Tender.
- **12.** Further particulars may be obtained from the undersigned on **Telephone No. 0094-11-2429451**

MANAGER - IMPORTS, THE ASSOCIATED NEWSPAPERS OF CEYLON LTD. E-Mail: imports@lakehouse.lk To: The Manager - Imports
The Associated Newspapers of Ceylon Ltd.,
No. 35, D.R. Wijewardene Mawatha,
Colombo 10.

## TENDER FOR THE SUPPLY OF FIRST CLASS WEB OFFSET NEWSPRINT PAPER IN REELS

			n Annex I, I/We hereby paper in Reels as follo		pply of							
01.	Name & Address	of Supplier/Principa		:								
02.	Name & Address Accredited Agent		:	i=								
03.	Name of the Man	ufacturing Mill	:	: <del>-</del>								
04.	Country of Origin		:	;								
05.	Quantity Offered		:	I <del>-</del>								
06.	Substance/Gramm	mage	:	·								
07.	Delivery Period		:									
08.	Terms of Paymen	nt	:	÷								
09.	CIF Price per M/	Гоn	:	÷								
		45 gsm L/C At Sight	28" (711 mm.) Any other Method of Payment	48.8 L/C At Sight	GSM (711 mm.) Any other Method of Payment							
F.O.E	3.											
Freig	jht											
Insu	rance											
	Гotal Colombo											
			14" (355 mm.) Any other Method of Payment	48.8 L/C At Sight	GSM (355 mm.) Any other Method of Payment							
F.O.E	3.											
Freig	ght											
Insu	rance											
	Гotal Colombo											
10.	Validity Period of	the Offer :										
11.	Bid bond No.:	of	for l	Rs. 100,000/- iss	ued by							
term		nd execute the orders	to supply the goods de s to the entire satisfact									
Date	:	Compar		Signature								

If the provided spaces are insufficient you may use annexure.

## **SPECIFICATIONS OF NEWSPRINT**

Quality : First Class Web Offset Newsprint Papers in Reels

2. Substance : Grammage GSM 48.8 (For colour printing)

GSM 45 (For B/W printing)

3. Inner Diameter of Core : 76 mm.

4. Reel Width : 711 mm.

355 mm.

5. Moisture Content : 45 GSM - 7% - 8%

48.8 GSM - 6.5% - 7%

6. PH Value : 5 - 6

7. Tensile Strength : M/D Not less than 2.20 KN/m

C/D Not less than 0.50 KN/m

8. Tear Strength : M/D Not less than 300 mN

C/D Not less than 325 mN

9. Opacity : Not less than 93%

10. ISO Brightness : Not less than 60%

11. Diameter of Reel : 965 mm. (minimum)

1016 mm. (maximum)

12. Ash content : Not more than 2%

13. Yellowness : 12% (maximum)

14. Core : High Compression Resistance

15. Core Plug : Compressed hardboard (non-collapsible) wood,

metal or hard plastic

16. Packing : Export packing in 3 - 4 sheets of thick cardboard with one

inner moisture barrier layer (water proof)

MANAGER/PRESS Press Department